

# HYDRA RAM<sup>®</sup>

ADVANCED DEMOLITION EQUIPMENT



HYDRAULIC SCRAP SHEARS  
HYDRAULIC ROTATING  
FULL RANGE FROM 1050 TO 12600 KG  
7 MODELS FOR CARRIERS FROM 12 TO 140 TONS

# HYDRA RAM®

ADVANCED DEMOLITION EQUIPMENT

## SPECIFICATIONS

MODEL	HSS-1000R	HSS-1600R	HSS-2500R	HSS-4000R
WEIGHT (kg)	1050	1600	2500	4000
OILFLOW (l/pm)	100-160	140-200	180-240	200-300
PRESSURE (bar)	300	300	300	320
JAW OPENING (mm)	330	360	500	600
JAW DEPTH (mm)	340	420	450	500
CUTTING FORCE (apex) (t)	60	80	120	130
CUTTING FORCE (center) (t)	120	150	200	220
OVERALL LENGTH (mm)	2000	2500	3000	3600
EXCAVATOR (2nd member) (t)	12-16	16-22	24-32	38-48
EXCAVATOR (1st member) (t)	8-12	10-16	16-22	24-32

MODEL	HSS-6000R	HSS-7500R	HSS-12000R
WEIGHT (kg)	6000	7500	12800
OILFLOW (l/pm)	250-350	300-400	350-450
PRESSURE (bar)	320	320	320
JAW OPENING (mm)	870	930	1100
JAW DEPTH (mm)	600	1000	1100
CUTTING FORCE (apex) (t)	160	180	280
CUTTING FORCE (center) (t)	300	350	490
OVERALL LENGTH (mm)	4000	4600	5200
EXCAVATOR (2nd member) (t)	52-70	65-90	110-140
EXCAVATOR (1st member) (t)	34-48	46-60	70-90

\* All models are Hydraulic Rotating



(DEALER)



**HYDRA RAM®**  
ADVANCED DEMOLITION EQUIPMENT

HYDRARAM b.v.  
Meander 7  
NL 9231DB SURHUISTERVEEN  
The Netherlands

tel. +31 512-365981  
fax. +31 512-365761  
www.hydraram.com  
info@hydraram.com

\*SPECIFICATIONS IN THIS BROCHURE ARE SUBJECT TO CHANGE WITHOUT NOTICE